

Locking Devices, Industrial, Female Connector Body, 30A 3-Phase Delta 250V AC, 3-Pole 4-Wire Grounding, L15-30R, Screw Terminal, Black and White

By Bryant
Catalog # [71530NC](#)



Locking Devices, Industrial, Female Connector Body, 30A 3-Phase Delta 250V AC, 3-Pole 4-Wire Grounding, L15-30R, Screw Terminal, Black and White

Features

- Face and body feature alignment keys for easy assembly
- Amperage, voltage and NEMA configuration imprinted on face for easy identification
- Impact/chemical resistant, toughened nylon construction
- Internal “self-centering” Triple Gripper® cord grip with “radius teeth” design provides secure cord retention

Application

Heavy Duty Industrial

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	L15-30R

Conductor

Number Of Conductors	4-Wire Grounding
Number Of Wires	4-Wire
Wire Size	#18 AWG to #8 AWG
Number Of Poles	3-Pole
Conductor Range	#12 AWG to #8 AWG

Current

Amperage Rating	30 A
Voltage Rating Description	3 Phase 250 VAC
Current/Amperage Rating Description	30 Amp
Current Rating	30 A
Voltage Rating	3 Phase 250 VAC

Connectivity

Screw Terminals

Dimensions

Length	2.13 in
Display Size	Standard Sized Product
Height	3.90 in
Width	2.13 in
Dimensions	2.13 in x 2.13 in x 3.90 in

General

Color	Black, White
Style	Internal Cord Clamp
OEM Brand Name	Hubbell Bryant
UPC	781786696198
Type	Connector Body
Material - Mounting Hardware	Cord Mounted
Insulation	Insulated Body
Item Type	30A Triple Gripper Nylon Connector
Material	Composite

Logistics

Pallet Quantity	1680
Carton Quantity	10

Operational

Temperature Rating	<ul style="list-style-type: none"> • Maximum Continuous: 75° C • Minimum Continuous: -40° C w/o impact, -25° with impact.
--------------------	---

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)