



# YS26LBOX, Cu Compression Splice, Standard Barrel, 2/0 AWG

By Burndy  
Catalog # [YS26LBOX](#)

2/0 AWG, CU, Standard Barrel SPLICE

## Features

- Copper seamless barrel with center stop indentations to indicate when wire is fully inserted into each side of the barrel
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors clearly marked with color coding

## Application

Wire Splice

## Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Buy America(n) Qualified	TAA Compliant (All status valid till December 2026)
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

## Conductor

Conductor - Material	COPPER
Wire Size	900 KCMIL
Conductor - Copper Str Size	900 KCMIL
Conductor - Copper Str Navy Size	125 (61) Navy
Conductor Size	2/0 AWG
Conductor - Copper Str Size Range	2/0 AWG
Conductor Type	CODE

## Configuration

Connector Type	STANDARD BARREL
----------------	-----------------

## Current

Voltage - Maximum	35000
Voltage Rating	35 kV

## Dimensions

Package Length	0.000 in
Package Width	0.000 in
Package Weight	0.000 lb.
Dimension - Outside Diameter inch	0.56 in
Dimension - L Length Overall mm	55 mm
Package Height	0.000 in
Dimension - Strip Length inch	1 in
Dimension - B Length fraction	15/16 in
Dimension - B Length inch	0.94 in
Dimension - Length Overall inch	2.17 in

## General

Die Index	13
Trade Name	HYLINK™
Sub Brand	HYLINK
Color Code	Black
Plated	Y
Feature - Barrel Type	Standard
Feature - Barrel Style	Chamfered
Type	YS-L, Standard Barrel
UPC 12 Digit	781810556252
UPC 14 Digit GTIN	00781810556252
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810556252

## Logistics

Minimum Pack Quantity	1
Carton Quantity	10

## Product Assets

[Catalog \[English\]](#)