



YS36L, Compression Splice, 600 kcmil Cu, Standard Barrel

By Burndy
Catalog # [YS36L](#)

600 kcmil, CU, Standard Barrel SPLICE

Features

- Copper seamless barrel with center stop indentations to indicate when wire is fully inserted into each side of the barrel
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors clearly marked with color coding

Application

Wire Splice

Specifications

Buy American Compliant Certification - cULus	Contact Manufacturer
EU RoHS Indicator	No
Certification - UL Recognized	Yes
Industry Standard(s)	No
Buy America(n) Qualified	UL 486A-486B
	TAA Compliant (All status valid till December 2026)
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Wire Size	600 kcmil
Conductor - Copper Str Size	600 kcmil
Conductor - Copper Str	600
Compact Size	
Conductor Size	600 KCMIL
Conductor - Copper Str Size	600 kcmil
Range	
Conductor Type	CODE

Configuration

Connector Type	STANDARD BARREL
----------------	-----------------

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Package Length	0.000 in
Package Width	0.000 in
Package Weight	0.000 lb.
Dimension - L Length Overall	82 mm
mm	
Package Height	0.000 in
Dimension - Strip Length inch	1-7/16
Dimension - B Length fraction	1-3/8 in
Dimension - B Length inch	1.38 in
Dimension - Length Overall	3.22 in
inch	

General

Die Index	22
Trade Name	HYLINK™
Sub Brand	HYLINK
Color Code	Green
Plated	Y
Feature - Barrel Type	Standard
Feature - Barrel Style	Chamfered
Type	YS-L, Standard Barrel
UPC 12 Digit	781810526408
UPC 14 Digit GTIN	00781810526408
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810526408

Logistics

Minimum Pack Quantity	1
Carton Quantity	6

Product Assets

[Catalog \[English\]](#)