

YS32L, Compression Splice, 400 kcmil Cu, Standard Barrel

By Burndy
Catalog # [YS32L](#)

400 kcmil, CU, Standard Barrel SPLICE



Features

- Copper seamless barrel with center stop indentations to indicate when wire is fully inserted into each side of the barrel
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors clearly marked with color coding

Application

Wire Splice

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Wire Size	400 kcmil
Conductor - Copper Str Size	400 kcmil
Conductor - Copper Str	400
Compact Size	
Conductor Size	400 KCMIL
Conductor - Copper Str Size	400 kcmil
Range	
Conductor Type	CODE

Configuration

Connector Type STANDARD BARREL

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Dimension - L Length Overall mm	70 mm
Dimension - Strip Length inch	1-1/4
Dimension - B Length fraction	1-3/16 in
Dimension - B Length inch	1.19 in
Dimension - Length Overall inch	2.74 in

General

Die Index	19
Trade Name	HYLINK™
Sub Brand	HYLINK
Color Code	Blue
Plated	Y
Feature - Barrel Type	Standard
Feature - Barrel Style	Chamfered
Type	YS-L, Standard Barrel
UPC 12 Digit	781810508459
UPC 14 Digit GTIN	00781810508459
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810508459

Logistics

Minimum Pack Quantity	1
Carton Quantity	6

Product Assets

[Catalog \[English\]](#)