

## YS5CLBOX, Compression Splice, 5 AWG Cu, Standard Barrel

By Burndy

Catalog # [YS5CLBOX](#)



5 AWG, CU, Standard Barrel SPLICE

### Features

- Copper seamless barrel with center stop indentations to indicate when wire is fully inserted into each side of the barrel
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors clearly marked with color coding

### Application

Wire Splice

### Specifications

Certification - cULus	No
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

### Conductor

Conductor - Material	COPPER
Wire Size	#5 AWG
Conductor - Copper Str Size	5 AWG
Conductor - Copper Str Navy Size	30 (19) Navy
Conductor Size	5 AWG
Conductor - Copper Str Size Range	5 AWG
Conductor Type	CODE

### Configuration

Connector Type	STANDARD BARREL
----------------	-----------------

### Current

Voltage - Maximum	35000
Voltage Rating	35 kV

### Dimensions

Dimension - Outside Diameter inch	0.30 in
Dimension - L Length Overall mm	48 mm
Dimension - Strip Length inch	7/8
Dimension - B Length fraction	13/16 in
Dimension - B Length inch	0.81 in
Dimension - Length Overall inch	1.90 in

### General

Die Index	7
Trade Name	HYLINK™
Color Code	Blue
Plated	Y
Feature - Barrel Type	Standard
Feature - Barrel Style	Chamfered
UPC 12 Digit	781810555606
UPC 14 Digit GTIN	00781810555606
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810555606

### Logistics

Minimum Pack Quantity	50
Carton Quantity	50

### Product Assets

[Catalog \[English\]](#)