

YS2CLBOX, Cu Compression Splice, Standard Barrel, 2 AWG

By Burndy

Catalog # [YS2CLBOX](#)



2 AWG, CU, Standard Barrel SPLICE

Features

- Copper seamless barrel with center stop indentations to indicate when wire is fully inserted into each side of the barrel
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors clearly marked with color coding

Application

Wire Splice

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Wire Size	#2 AWG
Conductor - Copper Str Size	2 AWG
Conductor - Copper Str Navy Size	60 (37) Navy
Conductor Size	2 AWG
Conductor - Copper Str Size Range	2 AWG
Conductor Type	CODE

Configuration

Connector Type	STANDARD BARREL
----------------	-----------------

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Dimension - Outside Diameter inch	0.42 in
Dimension - L Length Overall mm	51 mm
Dimension - Strip Length inch	15/16
Dimension - B Length fraction	7/8 in
Dimension - B Length inch	0.88 in
Dimension - Length Overall inch	2.00 in

General

Die Index	10
Trade Name	HYLINK™
Sub Brand	HYLINK
Color Code	Brown
Plated	Y
Feature - Barrel Type	Standard
Feature - Barrel Style Type	Chamfered
UPC 12 Digit	781810555255
UPC 14 Digit GTIN	00781810555255
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810555255

Logistics

Minimum Pack Quantity	1
Carton Quantity	25

Product Assets

[Catalog \[English\]](#)