

YS28LBOX, Cu Compression Splice, Standard Barrel, 4/0 AWG

By Burndy
Catalog # [YS28LBOX](#)



4/0 AWG, CU, Standard Barrel SPLICE

Features

- Copper seamless barrel with center stop indentations to indicate when wire is fully inserted into each side of the barrel
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors clearly marked with color coding

Application

Wire Splice

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Wire Size	#4/0 AWG
Conductor - Copper Str Size	4/0 AWG
Conductor - Copper Str Navy Size	200 (61) Navy
Conductor Size	4/0 AWG
Conductor - Copper Str Size Range	4/0 AWG
Conductor Type	CODE

Configuration

Connector Type	STANDARD BARREL
----------------	-----------------

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Dimension - Outside Diameter	0.69 inch
Dimension - L Length Overall	59 mm
Dimension - Strip Length	1-1/16 inch
Dimension - B Length fraction	1 in
Dimension - B Length	1.00 inch
Dimension - Length Overall	2.32 inch

General

Die Index	15
Trade Name	HYLINK™
Sub Brand	HYLINK
Color Code	Purple
Plated	Y
Feature - Barrel Type	Standard
Feature - Barrel Style	Chamfered
Type	YS-L, Standard Barrel
UPC 12 Digit	781810556757
UPC 14 Digit GTIN	00781810556757
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810556757

Logistics

Minimum Pack Quantity	1
Carton Quantity	10

Product Assets

[Catalog \[English\]](#)