

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Female, Receptacle, 60A 3-Phase Delta 480V AC, 3-Pole 4-Wire Grounding, Watertight

By Hubbell Wiring Device-Kellems
Catalog # [HBL460R7W](#)

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Female, Receptacle, 60A 3-Phase Delta 480V AC, 3-Pole 4-Wire Grounding, Terminal Screws, Red, Watertight

Features

- Self-closing gasketed cover
- Color coded housings for easy identification
- Super tough insulated non-metallic housing

Application

High Ampacity Watertight Connections

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstand 3000V AC, Electrical - Max. Working Voltage - 600V RMS, Environmental - Flammability - HB or better per UL 94 or CSA C22.2 No. 0.17, Environmental - Ingress Protection - IP67 Suitability, Environmental - Moisture Resistance - Watertight per IEC 60309-1, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum - 40°C w/o impact, Mechanical - Impact Resistance - Per CSA C22.2 No. 182.1 / UL1682, Mechanical - Product Identification - Ratings are a permanent part of the device housing, Mechanical - Terminal Identification - Terminals identified in accordance with North American and IEC conventions

Specifications

Environmental Conditions	Watertight
EU RoHS Indicator	Yes
Industry Standard(s)	Listed To Standard UL1682
Nema Rating	Non-NEMA

Conductor

Number Of Wires	4-Wire
Wire Size	#8 AWG to #2 AWG
Number Of Poles	3-Pole

Current

Current Rating	60 A
Amperage Rating	60 A
Voltage Rating Description	3 Phase 480 VAC
Phase	Three Phase
Current / Amperage Rating	60 A
Connectivity	Pressure Terminal Screws
Wattage	28800
Voltage Rating	3 Phase 480 VAC

Dimensions

Display Size	Standard Sized Product
--------------	------------------------

General

Series	HBL Heavy Duty
Style	Standard Service
Color	Red
Item Type	Single Flanged
Material - Mounting Hardware	Screw Mounting
Type	Watertight Receptacle
Material	Thermoplastic
Specifications	<ul style="list-style-type: none">• Cover - Reinforced Thermoplastic Polyester• Cover Screw - Nickel-plated brass• Gaskets - Solid Neoprene• Housing - Zytel® 101 Nylon• Mounting Flange - Zytel® 101 Nylon
UPC	783585404912

Logistics

Carton Quantity	10
Pallet Quantity	360

Product Assets

[Catalog \[English\]](#)

